

## NON-Hazardous Chemical, NON-Dangerous Goods

### 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: Hi Flex Construction

Synonyms

Hi-Flex Construction Black 600mls Hi-Flex Construction Grey 600mls Hi-Flex Construction White 600mls Product Code
HIFLEXCONSBL/SSG
HIFLEXCONSGR/SSG
HIFLEXCONSWH/SSG

**Recommended use:** Hi Flex Construction will bond to most common construction and industrial substrates such as aluminium and metals, masonry surfaces, natural stone and many plastics and is suitable for construction, manufacturing, automotive and marine industries.

Supplier: Adheseal ABN: 16 010 441 013

Street Address: 26 Wolverhampton Street

Stafford

Queensland 4053 **Telephone:** (07) 3356 0000 **Facsimile:** (07) 3356 0005

Email: sales@adheseal.com.au

Emergency Telephone number: (07) 3356 0000

### 2. HAZARDS IDENTIFICATION

Based on available information, this material is not classified as hazardous according to criteria of Safe Work Australia.

Poison Schedule: Not Applicable

### DANGEROUS GOOD CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

### 3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9 rich 1,2-Ethanediamine, N-[3-(dimethoxymethylsilyl)propyl]-Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)-Silane, ethenyltrimethoxy-Ingredients determined to be Non-Hazardous	68515-48-0 3069-29-2 22673-19-4 2768-02-7	10-30 % (w/w) <5 % (w/w) <1 % (w/w) <2 % (w/w) Balance

100%

### 4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800

Product Name: Hi Flex Construction Reference No: HIFLEXCONS
Issued: 2018-08-22 Version: Page 1 of 6



764 766).

**Inhalation:** Remove to fresh air. Get medical attention if symptoms persist

**Skin Contact:** wash with water and soap and rinse thoroughly.

Eye contact: Hold eyes open, flood with water for at least 15 minutes. Seek medical advice.

**Ingestion:** If swallowed, do not induce vomiting. Seek medical advice. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.

**PPE for First Aiders:** Wear gloves, safety glasses. Available information suggests that gloves made from should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. Treat symptomatically.

### 5. FIRE FIGHTING MEASURES

Hazchem Code: Not applicable.

**Suitable extinguishing media:** If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Non-combustible material.

Fire fighting further advice: Not applicable.

### 6. ACCIDENTAL RELEASE MEASURES

### **SMALL SPILLS**

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

#### LARGE SPILLS

Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of dust. Work up wind or increase ventilation. Cover with damp absorbent (inert material, sand or soil). Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: Not applicable

### 7. HANDLING AND STORAGE

Handling: Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of dust.

**Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Keep container standing upright. Keep containers closed when not in use - check regularly for spills.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Product Name: Hi Flex Construction Reference No: HIFLEXCONS

Issued: 2018-08-22 Version: Page 2 of 6



National occupational exposure limits: No value assigned for this specific material by Safe Work Australia.

**Biological Limit Values:** As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Natural ventilation should be adequate under normal use conditions.

Personal Protection Equipment: GLOVES, SAFETY GLASSES.

Personal protective equipment (PPE) must be suitable for the nature of the work and any hazard associated with the work as identified by the risk assessment conducted.

Wear gloves, safety glasses. Available information suggests that gloves made from should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Hygiene measures:** Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of dust. Ensure that eyewash stations and safety showers are close to the workstation location.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Material Family:UnknownBase Units:LitresForm:Paste

**Colour:** Various Colours **Odour:** slight odour

**Solubility:** immiscible in water

Solubility in water: Insoluble

Density:

Vapour Pressure (20 °C):

Flash Point (°C):

Flammability Limits (%):

Autoignition Temperature (°C):

Melting Point/Range (°C):

Approx 1.45 +/-.05

Not Available

Not Available

Not Available

Pour Point/Range (°C): > 0

Decomposition Point (°C):Not AvailableSublimation Point (°C):Not AvailablepH:Not AvailableViscosity:Not Available

Total VOC (g/Litre): < 5 %

(Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable

### 10. STABILITY AND REACTIVITY

**Chemical stability:** Stable under normal room temperature.

Conditions to avoid: None Known

Issued: 2018-08-22

Incompatible materials: None Known

Product Name: Hi Flex Construction Reference No: HIFLEXCONS

Version: Page 3 of 6



Hazardous decomposition products: None Known

Hazardous reactions: Under normal conditions of storage and use, hazardous reactions will not occur.

### 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

### **Acute Effects**

Inhalation: Inhalation may cause irritation to respiratory system.

**Skin contact:** May cause mild irritation to skin.

**Ingestion:** Harmful if swallowed. see medical attention.

**Eye contact:** Irritation to eye Exposure to the dust may cause discomfort due to particulate nature. May cause physical irritation to the eyes.

### **Acute toxicity**

**Inhalation:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): LC50 > 5 mg/L

**Skin contact:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg bw

LD50 (Rat): 3500mg

**Ingestion:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg bw

LD50 (Rat): > 11,000 mg/Kg

**Corrosion/Irritancy:** Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as not corrosive or irritating to skin.

**Sensitisation:** Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as not a skin sensitiser.

Aspiration hazard: This material has been classified as non-hazardous.

Specific target organ toxicity (single exposure): This material has been classified as non-hazardous.

**Chronic Toxicity** 

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

### 12. ECOLOGICAL INFORMATION

Product Name: Hi Flex Construction Reference No: HIFLEXCONS

Issued: 2018-08-22 Version: Page 4 of 6



Page 5 of 6

Avoid contaminating waterways.

Acute aquatic hazard: information is not available.

Long-term aquatic hazard: information is not available.

Ecotoxicity: information is not available.

Persistence and degradability: information is not available.

Bioaccumulative potential: No information available.

**Mobility:** Low mobility in soil.

### 13. DISPOSAL CONSIDERATIONS

Must be disposed according to state or local official regulations.

### 14. TRANSPORT INFORMATION

### **ROAD AND RAIL TRANSPORT**

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

### MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

### AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

### 15. REGULATORY INFORMATION

### This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)

The Stockholm Convention (Persistent Organic Pollutants)

The Rotterdam Convention (Prior Informed Consent)

Basel Convention (Hazardous Waste)

International Convention for the Prevention of Pollution from Ships (MARPOL)

#### 16. OTHER INFORMATION

Reason for issue: Revised

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

**Product Name: Hi Flex Construction** Reference No: HIFLEXCONS Issued: 2018-08-22 Version:



Safety Data Sheets are updated frequently. Please ensure you have a current copy.

Product Name: Hi Flex Construction Reference No: HIFLEXCONS
Issued: 2018-08-22 Version: Page 6 of 6