# SAFETY DATA SHEET

# 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name

**KEMGROUT SANDED** 

Synonym(s)

KEM GROUT SANDED · SANDED KEMGROUT

1.2 Uses and uses advised against

Use(s)

**GROUT • TILE GROUT** 

1.3 Details of the supplier of the product

Supplier name

DRIBOND CONSTRUCTION CHEMICALS

Address

49-57 Davis Street, Wingfield, SA, 5013, AUSTRALIA

Telephone

(08) 8243 7888

Fax

(08) 8243 7800

Email

info@constructionchemicals.com.au

Website

www.constructionchemicals.com.au

1.4 Emergency telephone number(s)

**Emergency** 

(08) 8243 7888

# 2. HAZARDS IDENTIFICATION

## 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO AUSTRALIAN WHS REGULATIONS

GHS classification(s)

Skin Corrosion/Irritation: Category 2

Serious Eye Damage / Eye Irritation: Category 2A

Specific Target Organ Systemic Toxicity (Single Exposure): Category 3

2.2 Label elements

Signal word

WARNING

Pictogram(s)



Hazard statement(s)

H315 Causes skin irritation.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

Prevention statement(s)

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

ChemAlert.

SDS Date: 22 Aug 2016

### Response statement(s)

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P321 Specific treatment is advised - see first aid instructions.
P332 + P337 + P313 If skin or eye irritation occurs: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before re-use.

Storage statement(s)

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal statement(s)

P501 Dispose of contents/container in accordance with relevant regulations.

2.3 Other hazards

No information provided.

# 3. COMPOSITION/ INFORMATION ON INGREDIENTS

### 3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
ADDITIVE(S)	-	•	Remainder
PORTLAND CEMENT	65997-15-1	266-043-4	30 to 60%
OXIDE PIGMENTS	•	_	Not Available
SAND, AMORPHOUS	-	•	Not Available

## 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

Eye If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to

stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If

swallowed, do not induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

# 4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

Ingestion

## 5. FIRE FIGHTING MEASURES

# 5.1 Extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

## 5.2 Special hazards arising from the substance or mixture

Non flammable. May evolve toxic gases if strongly heated.

# 5.3 Advice for firefighters

No fire or explosion hazard exists.

# 5.4 Hazchem code

None allocated.

ChemAlert.

SDS Date: 22 Aug 2016

## 6. ACCIDENTAL RELEASE MEASURES

## 6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Contact emergency services where appropriate.

### 6.2 Environmental precautions

Prevent product from entering drains and waterways.

### 6.3 Methods of cleaning up

Contain spillage, then collect and place in suitable containers for reuse or disposal. Avoid generating dust.

### 6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

# 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from moisture, incompatible substances and foodstuffs. Ensure packages are adequately labelled, protected from physical damage and sealed when not in use.

### 7.3 Specific end use(s)

No information provided.

## **EXPOSURE CONTROLS / PERSONAL PROTECTION**

### 8.1 Control parameters

# **Exposure standards**

Ingredient	Reference	TWA		STEL	
aigrodient		ppm	mg/m³	ppm	mg/m³
Portland Cement	SWA (AUS)		10		•••

## **Biological limits**

No biological limit values have been entered for this product.

### 8.2 Exposure controls

**Engineering controls** Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction

ventilation is recommended. Maintain dust levels below the recommended exposure standard.

PPE

Wear dust-proof goggles. Eye / Face Hands Wear PVC or rubber gloves.

Body When using large quantities or where heavy contamination is likely, wear coveralls.

Respiratory Where an inhalation risk exists, wear a Class P1 (Particulate) respirator. At high dust levels, wear a

Powered Air Purifying Respirator (PAPR) with Class P3 (Particulate) filter or a Class P3 (Particulate)

respirator.



# PHYSICAL AND CHEMICAL PROPERTIES

## 9.1 Information on basic physical and chemical properties

**Appearance** 

COLOURED POWDER



SDS Date: 22 Aug 2016 Version No: 1

Page 3 of 7

9.1 Information on basic physical and chemical properties

Odour SLIGHT ODOUR Flammability NON FLAMMABLE Flash point **NOT RELEVANT Boiling point** NOT AVAILABLE Melting point NOT AVAILABLE Evaporation rate NOT AVAILABLE рΗ 11 (1% solution) **NOT AVAILABLE** Vapour density

Specific gravity 3

Solubility (water) SLIGHTLY SOLUBLE Vapour pressure **NOT AVAILABLE** Upper explosion limit **NOT RELEVANT** Lower explosion limit **NOT RELEVANT** Partition coefficient **NOT AVAILABLE** Autoignition temperature **NOT AVAILABLE Decomposition temperature NOT AVAILABLE** Viscosity **NOT AVAILABLE Explosive properties NOT AVAILABLE** Oxidising properties **NOT AVAILABLE NOT AVAILABLE** Odour threshold

# 10. STABILITY AND REACTIVITY

### 10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

### 10.2 Chemical stability

Stable under recommended conditions of storage.

### 10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

### 10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

### 10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), ethanol, acids (e.g. hydrofluoric acid) and interhalogens (e.g. chlorine trifluoride). Water contact may increase product temperature 2°C to 3°C.

## 10.6 Hazardous decomposition products

May evolve toxic gases if heated to decomposition.

## 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

Information available for the product: Acute toxicity

Based on available data, the classification criteria are not met.

Skin Contact with powder or wetted form may result in irritation, rash and dermatitis.

Contact may result in irritation, lacrimation, pain, redness, corneal burns and possible permanent damage. Eye

Sensitisation Not classified as causing respiratory sensitisation. However, some individuals may exhibit an allergic response upon exposure to cement, possibly due to trace amounts of chromium.

Mutagenicity Insufficient data available to classify as a mutagen.

This product may contain trace amounts of crystalline silica and hexavalent chromium which are classified as Carcinogenicity

carcinogenic to humans (IARC Group 1). There is sufficient information to conclude that the relative risk of lung cancer from exposure to crystalline silica is increased in persons with silicosis. Therefore, preventing

the onset of silicosis will also reduce the cancer risk.

Insufficient data available to classify as a reproductive toxin. Reproductive

STOT - single

Over exposure may result in irritation of the nose and throat, with coughing.

exposure

STOT - repeated Not classified as causing organ damage from repeated exposure.

exposure

SDS Date: 22 Aug 2016 Version No: 1

Page 4 of 7



Aspiration

This product is a solid and aspiration hazards are not expected to occur.

## 12. ECOLOGICAL INFORMATION

## 12.1 Toxicity

No information provided.

## 12.2 Persistence and degradability

No information provided.

### 12.3 Bioaccumulative potential

No information provided.

### 12.4 Mobility in soil

No information provided.

### 12.5 Other adverse effects

No information provided.

# 13. DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

Waste disposal

Reuse or recycle where possible. Alternatively, ensure product is covered with moist soil to prevent dust generation and dispose of to an approved landfill site. Contact the manufacturer/supplier for additional

information (if required).

Legislation

Dispose of in accordance with relevant local legislation.

## 14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	None Allocated	None Allocated	None Allocated
14.2 Proper Shipping Name	None Allocated	None Allocated	None Allocated
14.3 Transport Hazard Class	None Allocated	None Allocated	None Allocated
14.4 Packing Group	None Allocated	None Allocated	None Allocated

14.5 Environmental hazards No information provided

### 14.6 Special precautions for user

Hazchem code

None Allocated

## 15. REGULATORY INFORMATION

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the

Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and

Labelling of Chemicals.

The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous

Substances [NOHSC: 1008(2004)].

Hazard codes

Χi

Irritant

Risk phrases

R36/37/38

Irritating to eyes, respiratory system and skin.

Page 5 of 7

ChemAlert.

SDS Date: 22 Aug 2016

Safety phrases S22 Do not breathe dust.

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S28 After contact with skin, wash immediately with plenty of water.
S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

Inventory listing(s) AUSTRALIA: AICS (Australian Inventory of Chemical Substances)

All components are listed on AICS, or are exempt.

## 16. OTHER INFORMATION

### Additional information

CEMENT CONTACT DERMATITIS: Individuals using wet cement, mortar, grout or concrete could be at risk of developing cement dermatitis. Symptoms of exposure include itchy, tender, swollen, hot, cracked or blistering skin with the potential for sensitisation. The dermatitis is due to the presence of soluble (hexavalent) chromium.

IARC - GROUP 1 - CONFIRMED HUMAN CARCINOGEN. This product contains an ingredient for which there is sufficient evidence to have been classified by the International Agency for Research into Cancer as a human carcinogen. The use of products known to be human carcinogens should be strictly monitored and controlled.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

## HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate,

### **Abbreviations**

ACGIH American Conference of Governmental Industrial Hygien	enists
---	--------

CAS # Chemical Abstract Service number - used to uniquely identify chemical compounds

CNS Central Nervous System

EC No. EC No - European Community Number

EMS Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous

Goods)

GHS Globally Harmonized System

GTEPG Group Text Emergency Procedure Guide IARC International Agency for Research on Cancer

LC50 Lethal Concentration, 50% / Median Lethal Concentration

LD50 Lethal Dose, 50% / Median Lethal Dose

mg/m³ Milligrams per Cubic Metre
OEL Occupational Exposure Limit

pH relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly

alkaline).

ppm Parts Per Million

STEL Short-Term Exposure Limit

STOT-RE Specific target organ toxicity (repeated exposure)
STOT-SE Specific target organ toxicity (single exposure)

SUSMP Standard for the Uniform Scheduling of Medicines and Poisons

SWA Safe Work Australia
TLV Threshold Limit Value
TWA Time Weighted Average



SDS Date: 22 Aug 2016

### Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794

Email: info@rmt.com.au Web: www.rmt.com.au.

[ End of SDS ]

Chem/Alert.

SDS Date: 22 Aug 2016