### ifety Data Sheet KERACOLOR FF FLEX

Safety Data Sheet dated: 2/13/2019 - version 3

Date of first edition: 5/3/2017



#### 1. Identification

#### **GHS** Product identifier

Mixture identification:

Trade name: KERACOLOR FF FLEX

Trade code: 905N100

Recommended use of the chemical and restrictions on use

Recommended use: Ready prepared cement mortar

Uses advised against: no data available

Supplier's details

Company: MAPEI AUSTRALIA Pty Ltd

180 Viking Drive Wacol QLD 4076 Australia T. +61 7 32765000 (Mon-Fri 8am to 4.30pm)

F. +61 7 32765076

**Emergency phone number** Australian Poisons Information Centre 24 Hour Service 13 11 26

Police or Fire Brigade 000

#### 2. Hazard identification





#### Classification of the Hazardous chemical

Skin Irrit, 2 Causes skin irritation.

Eye Dam. 1 Causes serious eye damage.

Skin Sens. 1B May cause an allergic skin reaction.

STOT SE 3 May cause respiratory irritation.

Adverse physicochemical, human health and environmental effects:

No other hazards

### GHS label elements, including precautionary statements

### Pictograms and Signal Words



Danger

#### Hazard statements:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

### Precautionary statements:

P261 Avoid breathing dust.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

Date 3/8/2019 Production Name KERACOLOR DE ELEX Page # 1 of 8 to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

If skin irritation occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with applicable regulations.

### Other hazards which do not result in a classification

Other Hazards: No other hazards

This preparation contains cement. Cement gives a strong alkaline reaction with water and body fluids (e.g. sweat and eye fluids). It may cause irritation or burns.

#### 3. Composition/information on ingredients

#### Substances

no data available

#### Mixtures

# Hazardous components within the meaning of the "Australian Work Health and Safety (WHS)" regulation and related classification:

Quantity	Name	Ident. Numb.	Classification	Registration Number
25 - <50 %	Portland cement, Cr(VI) < 2 ppm		Skin Irrit. 2, H315; Skin Sens. 1B, H317; Eye Dam. 1, H318; STOT SE 3, H335	
≥10 - <20 %	calcium carbonate	CAS:1317-65-3 EC:215-279-6		
≥1 - <2.5 %	calcium hydroxide	CAS:1305-62-0 EC:215-137-3	Skin Irrit. 2, H315; Eye Dam. 1, H318; STOT SE 3, H335	01-2119475151-45-XXXX

#### 4. First-aid measures

### Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

#### Symptoms caused by exposure

Eye irritation

Eye damages

Skin Irritation

Erythema

### Medical attention and special treatment

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

### 5. Fire-fighting measures

#### Suitable extinguishing media

None in particular.

Date 3/8/2019 Production Name KERACOLOR FF FT FX Page n 2 of 8

Water.

Carbon dioxide (CO2).

#### Poecific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: no data available

Explosive properties: no data available Oxidizing properties: no data available

#### Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

#### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

#### environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

#### Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

### 7. Handling and storage

#### Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

### Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

### 8. Exposure controls/personal protection

Control parameters - exposure standards, biological monitoring

### List of components with OEL value

	Component	OEL Type	Country Co	_	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Behaviour	Note
ger.	ralcium carbonate	ACGIH	NNN		10					

alcium hydroxide OSHA 15

OSHA 5 ACGIH 5

eye, skin and upper respiratory tract irritation;

AUS AUSTRALIA

0 11001101211

### Predicted No Effect Concentration (PNEC) values

. . . . . .

Component	CAS-No.	PNEC LIMIT	Exposure Route	Exposure Frequency	Remark
calcium hydroxide	1305-62-0	0,49 mg/l	Fresh Water		
		1080 mg/kg	Soil		
		0,32 mg/l	Marine water		
		3 mg/l	Microorganisms in sewage treatments		

#### Derived No Effect Level. (DNEL)

Component	CAS-No.	Worker Industr y		Exposure Route	Exposure Frequency Remark
calcium hydroxide	1305-62-0	4 mg/m3	4 mg/m3	Human Inhalation	Short Term, local effects
		1 mg/m3	1 mg/m3	Human Inhalation	Long Term, local effects

#### Appropriate engineering controls

no data available

#### Individual protection measures, such as personal protective equipment (PPE)

Eve protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

### Physical and chemical properties

Color: various Appearance: Powder

Odour: slight, typical of cement Odour threshold: no data available pH in water dispersion: 12.00

Melting point / freezing point: no data available

Initial boiling point and boiling range: no data available

Flash point: no data available Evaporation rate: no data available Flammability (Solid, Gas): no data available

Upper/lower flammability or explosive limits: no data available

Vapour pressure: no data available Vapour density: no data available Relative density: 1.30 g/cm3 Solubility in water: partly soluble Solubility in oil: Insoluble

Partition coefficient (n-octanol/water): no data available

Auto-ignition temperature: no data available Decomposition temperature: no data available

Date 378/2019 Production Name KERACOLOR EFIFLEX Page n 4 of 8

Viscosity: no data available

Specific heat value: no data available

Saturated vapour concentration: no data available

Release of invisible flammable vapours and gases: no data available

Particle size: no data available Size distribution: no data available Shape and aspect ratio: no data available

Crystallinity: no data available Dustiness: no data available Surface area: no data available

Degree of aggregation or agglomeration, and dispersibility: no data available

Biodurability or biopersistence: no data available Surface coating or chemistry: no data available VOC (Volatile Organic Compound): 0 (Rule 1168) g/l

#### 10. Stability and reactivity

#### Reactivity

Stable under normal conditions

#### Chemical stability

no data available

#### Possibility of hazardous reactions

None.

#### Conditions to avoid

Stable under normal conditions.

#### Incompatible materials

None in particular.

Hazardous decomposition products

### **SECTION 11: Toxicological information**

Information on toxicological effects

#### Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

### Toxicological information on main components of the mixture:

alcium carbonate

a) acute toxicity

LD50 Oral Rat > 2000 mg/kg

calcium hydroxide

a) acute toxicity

LD50 Oral Rat > 2000 mg/kg LD50 Skin Rabbit > 2500 mg/kg

LD50 Oral Rat = 7340 mg/kg

### If not differently specified, the information required in the regulation and listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure
- i) STOT-repeated exposure
- j) aspiration hazard

Date 3/8/2019 Production Name KERACOLOR FF FT FX Page r - 5 of -8

#### 2. Ecological information

#### **\_cotoxicity**

Adopt good working practices, so that the product is not released into the environment. Eco-Toxicological Information:

List of componer	nts with eco-toxicological p	properties		
Quantity	Component	Ident. Numb.	Ecotox Infos	
>=10 - <20 %	calcium carbonate	CAS: 1317-65-3 - EINECS: 215- 279-6	a) Aquatic acute toxicity :	EC50 Daphnia > 1000 mg/L 48
			a) Aquatic acute toxicity :	EC50 Algae > 200 mg/L 72
			a) Aquatic acute toxicity :	EC50 Fish > 10000 mg/L 96
>=1 - <2.5 %	calcium hydroxide	CAS: 1305-62-0 - EINECS: 215- 137-3	a) Aquatic acute toxicity :	EC50 Daphnia = 49,1 mg/L 48
			a) Aquatic acute toxicity :	EC50 Algae = 184,57 mg/L 72
			a) Aquatic acute toxicity :	LC50 Fish = 457 mg/L 96
			a) Aquatic acute toxicity :	LC50 Fish = 50,6 mg/L 96

a) Aquatic acute toxicity: LC50 Daphnia = 158 mg/L 96 b) Aquatic chronic toxicity: NOEC Algae = 48 mg/L 72 b) Aquatic chronic toxicity: NOEC Daphnia = 32 mg/L - 14 d

d) Terrestrial toxicity: NOEC = 2000 mg/kg e) Plant toxicity: NOEC = 1080 mg/kg - 21 d

#### Persistence and degradability

no data available

### **Bioaccumulative** potential

no data available

## Mobility in soil

no data available

#### Other adverse effects

no data available

#### 13. Disposal considerations

### isposal methods

recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

### 14. Transport information

Not classified as dangerous in the meaning of transport regulations.

**UN number** 

no data available

UN proper shipping name

no data available

Transport hazard class(es)

no data available

Packing group, if applicable

no data available

**Environmental hazards** 

no data available

Special precautions for user

o data available

Additional Information

Date 3/8/2019 Production Name: KERACOLOR DE FLEX Pager 6 of X no data available

#### HazChem Code/Emergency Action code

no data available

### 15. Regulatory information

### Safety, health and environmental regulations specific for the product in question

This Safety Data Sheet has been prepared according to the Australian Work Health and Safety (WHS) act and the Code of Practice on preparation of safety data sheets for Hazardous Chemicals.

AICS: all components are listed

#### 16. Other information

Code Description
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.

May cause respiratory irritation.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

335

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures) BCF: Biological Concentration Factor BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.
CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand COV: Volatile Organic Compound CSA: Chemical Safety Assessment

BOD: Biochemical Oxygen Demand

CSR: Chemical Safety Report DMEL: Derived Minimal Effect Level DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive DSD: Dangerous Substances Directive EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

Date 3/8/2019 Production Name | REBACQLORIFITIEX | Page n | 7 | of | 8

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low N.A.: Not Applicable N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration.

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.

#### Paragraphs modified from the previous revision:

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 16. OTHER INFORMATION

Date 3/8/2019 Production Name KERACOLOR FF FLEX Page n 8 of 8