

Review Date: 19/2/2025

Original Document Date: 25/10/23

Classified as hazardous according to criteria of Worksafe Australia

Section 1: Identification of the substance/mixture and of the company

1:1 Product Identifier

Product Name: TTC QLD Urban Domestic Tile

Adhesive

Other Names: None Product Code: TTCQDOM

1:2 Relevant identified uses of the product

Application: A Premium Powder Mastic for wall &

floor tiling applications.

1.3 Supplier details

Supplier: TTC QLD Pty Ltd

(ABN: 30 306 671 905)

Address: Unit 3, 13-15 Fishermans Rd Kuluin

QLD 4558

Phone: (07) 5443 9191 Emergency Phone: (07) 5443 9191

The information contained in this safety data sheet is accurate on the date of issue and in accordance with the information available at that time. Persons dealing with products referred to in this safety data sheet do so at their own risk. TTC QLD Pty Ltd accepts no liability whatsoever for damage or injury, however caused, arising from use of this information or of suggestions contained herein.

Section 2: Hazard Identification

2:1 Classification of product

Skin Corrosion/Irritation: Category 2 (H315)

Serious Eye Damage / Eye Irritation: Category 2A (H319)

Specific Target Organ Toxicity - Single Exposure: Category 3 Respiratory Irritation

(H335)

Carcinogenicity: Category 1A (H350i)

Specific Target Organ Toxicity (Repeated Exposure): Category 2 (H373)

Dust may irritate throat and respiratory system and cause coughing.

Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases. Dust or splashes from the mixture may cause permanent eye damage.

Dust has an irritating effect on moist skin. Prolonged contact with wet cement/mixture may cause burns.







Original Document Date: 25/10/23



Signal Word: **DANGER**

Hazard Statements:

H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H350i	May cause cancer by inhalation
H373	May cause damage to organs through prolonged or repeated exposure

Precautionary Statements:

Precautionary Statements:		
P203	Obtain, read and follow all safety instructions before use.	
P260	Do not breathe dust	
P280	Wear protective gloves, mask, eye and face protection	
P264 + P265	Wash skin thoroughly after handling. Do not touch eyes.	
P271	Use in well-ventilated area	
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several	
1 000 11 001 11 000	minutes. Remove contact lenses if present and easy to do - continue rinsing.	
P337+P317	If EYE irritation persists: Get medical help.	
P302+P352	IF ON SKIN: Gently wash with plenty of soap and water.	
P332+P317	IF SKIN irritation occurs: Get medical advice/attention.	
P362+P364	Take off contaminated clothing and wash it before reuse.	
P318	If exposed or concerned, get medical advice.	
P319	Get medical help if you feel unwell	
P501	Dispose of contents/container in accordance with local regulations	

2.3 Other hazards Other hazards: N/A

Section 3: Composition/Information on Ingredients

3:1 Mixtures

This product contains cement

This product contains comont			
Chemical Name	CAS-No.	%	Hazard Classification
Portland Cement	65997-15-1	30-40%	STOT SE HC-3
			Skin Irritation HC-2
			Eye Irritation HC-2
			STOT RE HC-2



Review Date: 19/2/2025

Original Document Date: 25/10/23

Bentonite	14808-60-7 & 14464-46-1		Carcinogenicity HC-1A STOT RE HC-2
Non Hazardous Ingredients	N/A	Balance	N/A

Section 4: First Aid Measures

4:1 Description of first aid measures

Inhalation: Move subject to fresh air. Monitor and

consult a physician if concerned

Skin Contact: Wash affected areas thoroughly with

soap & water. Consult a physician if

irritation persists

Eye Contact: Flush eyes with large amount of water

for at least 15 minutes, holding eyelids apart. Consult a physician if irritation

persists

Ingestion: Flush mouth with copious amounts of

water. Consult a physician.

4:2 Symptoms caused by exposure

Inhalation: Dust may irritate airway and cause

coughing

Skin Contact: Dust may irritate moist skin

Prolonged exposure could result in allergic reaction such as a rash or

burning sensation

Eye Contact: Contact with eye can cause

permanent eye damage - immediately

seek first aid

Ingestion: Can cause irritation to the throat and

stomach

4:3 Medical Attention and Special Treatment

N/A

Section 5: Fire Fighting Measures

5:1 Suitable extinguishing media

This is a non-flammable material. Use suitable extinguishing media for the surrounding area.

5:2 Specific hazards

None Applicable

5:3 Special protective equipment and precautions for fire fighters

Chemical resistant clothing should be used along with respiratory protection.



Review Date: 19/2/2025

Original Document Date: 25/10/23

Section 6: Accidental Release Measures

6:1 Personal precautions, protective equipment and emergency procedures

Wear appropriate clothing, gloves, eye protection and facemask to avoid inhalation and contact with skin or eyes.

Emergency Procedures: N/A 6:2 Environmental precautions

Do not allow this product to be released into storm water drains, creeks, or open bodies of water. Dispose in accordance with local regulations.

6:3 Methods and materials for contaminant and cleaning up

In dry form: Vacuum where possible. Sweep with a brush or broom.

In wet form: Cover any drains and wipe product with a cloth. Dispose in accordance

with local regulations.

Section 7: Handling and Storage

7:1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid dust.

7:2 Conditions for safe storage, including any incompatibilities

Store in a cool dry location in a closed container to avoid dust.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up. Incompatibilities: N/A

Section 8: Exposure Controls and Personal Protection

8:1 Control parameters

The exposure limits for ingredients are listed below

Chemical Name	CAS No.	Exposure Limit	Туре	References
Portland Cement – respirable dust	65997-15-1	3 mg/m ³	TWA	USECHH 2000
Portland Cement – inhalable dust	65997-15-1	10 mg/m ³	TWA	USECHH 2000
Bentonite no exposure value assigned				
Crystalline Silica	14808-60-7	0.1mg/m3	TWA	Safe Work Australia
(Respirable Dust)				

8:2 Exposure controls

Provide adequate ventilation. Observe occupational exposure limits and minimise risk of inhalation & contact with skin & eyes

8:3 Personal protective equipment (PPE)

Wear protective gloves

Wear goggles/face shield

Wear protective clothing including boots

Face protection should be used in connection with splashing work

Use respiratory equipment with particle filter during dust raising work

The use of barrier cream is recommended



Review Date: 19/2/2025

Original Document Date: 25/10/23

Remove all contaminated PPE carefully to avoid contact with skin or eyes. Wash contaminated clothing thoroughly before reuse. Wash skin with soap and water after work

Environmental exposure controls: Not available

Section 9: Physical and Chemical Properties

9:1 Physical and chemical properties

9. I Physical and Chemica	
Appearance:	Off White Powder
Odour:	Cement
Odour threshold:	N/A
pH:	Alkaline (approx. 12 when mixed with water)
Flash point:	Non-combustible
Flammability limits:	Not Available
Solubility in water:	Miscible in water
Stability:	Stable
Vapour pressure:	Not Available
Specific gravity:	3
Volatile component:	N/A
Auto ignition temp	N/A

Section 10: Stability & Reactivity

10:1 Reactivity

None known

10:2 Chemical stability

Product is stable under normal temperature conditions

10:3 Conditions to avoid

See incompatible materials

10:4 Incompatible materials and possible hazardous reactions

Incompatible materials: None Known

Hazardous reactions: N/A

10:5 Hazardous decomposition products

N/A

Review Date: 19/2/2025

Original Document Date: 25/10/23



Section 11: Toxicological Information

11:1 Information and symptoms related to exposure

Acute Toxicity:	No data available
Skin corrosion/irritation:	Repeated or prolonged exposure to skin can cause dermatitis
Serious eye damage/irritation:	Exposure can cause serious conjunctivitis, blepharitis, and general irritation to the eyes. Dust or splashes from the mixture may cause permanent eye damage. Immediate first aid is necessary.
Respiratory & Ingestion	Dust can irritate airways. Prolonged exposure may cause coughing or wheezing. Ingestion of product may irritate the gastric tract and cause nausea & vomiting
Germ Cell Mutagenicity:	No data available
Carcinogenicity:	May cause cancer by inhalation.
Reproductive Toxicity:	No data available

Specific Target Organ Toxicity (STOT)		
Single Exposure:	Can cause coughing and irritation to airway	
Repeated Exposure:	Repeated exposure over a long period of time may cause coughing and phlegm, shortness of breath and wheezing. Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases & cancers.	
Aspiration Hazard:	No data available	

11.2 Numerical measures of toxicity

No data available

11.3 Immediate, delayed or chronic health effects from exposure

Immediate:	Irritation of the skin, eyes & respiratory tract
Delayed:	Allergic skin reaction, irritation, coughing wheezing & possible injury to eyes
Chronic:	Increased chance of bronchitis, conjunctivitis, ulcers of the nose & dermatitis

11.4 Exposure levels

Exposure levels: See section 8:1

11.5 Interactive effects

Inhalation:	Respiratory conditions such as asthma can increase risk of coughing and wheezing.
Skin contact:	Sensitivity of the skin can lead to greater risk of allergic skin reactions

11.6 Data limitations

Data limitations: N/A



Review Date: 19/2/2025

Original Document Date: 25/10/23

Section 12: Ecological Information

12:1 Ecotoxicity

This product is not expected to be hazardous to the environment

12:2 Degradability

When mixed with water this product will form to a hard mass that is non-degradable

12:3 Bio-accumulative potential

No data available

12:4 Mobility in soil

No data available

12:5 Other adverse effects

None known

Section 13: Disposal Considerations

Section 13:1 Safe disposal of product and packaging

P501 Dispose of contents & container waste in accordance with local regulations Waste is considered hazardous. However, product hardened with water is considered non-hazardous.

Packaging is recyclable when all traces of material have been cleaned from bag Do not allow product to enter sewerage system of storm water drain, this will block pipes

Section 14: Transport Information

14:1 UN number:None allocated14:2 Proper shipping name:None allocated14:3 Transport hazard class:None allocated14:4 Packaging group:None allocated

14:5 Environmental hazards:N/A14:6 Special transport precautions:N/A14:7 Hazchem code:N/A

Section 15: Regulatory Information

15:1 Safety, health and environmental regulations specific to the product

N/A

15:2 Poisons schedule number

N/A



Review Date: 19/2/2025

Original Document Date: 25/10/23

Section 16: Regulatory Information

This SDS has been reviewed 19th February 2025. This SDS will be reviewed every 5 years. The latest version of this SDS will be available for download from https://www.tilerstradecentre.com.au/ This SDS may change from time to time as new information becomes available or in the case of a change in formulation. This SDS is has been prepared as a new document to bring into line with Globally Harmonized System requirements.

16:2 Abbreviations and acronyms used in this SDS

GHS = Globally Harmonized System

HC - = Hazard Category

CAS = Chemical Abstract Service

N/A = Not Applicable

TWA = Time Weighted Average

USECHH = Use and Standard of Exposure Chemical Hazardous to Health.

STOT = Specific Target Organ Toxicity

STOT SE = Specific Target Organ Toxicity – Single Exposure

STOT RE = Specific Target Organ Toxicity – Repeated Exposure

mg/m3 = milligram per cubic metre

This SDS has been prepared using information provided by the manufactures of the ingredients contained in this product. This product is a mixture of ingredients.

.... END OF SDS

This SDS has been developed in accordance to Worksafe Australia/NOHSC guidelines