

Davco



Product Data Sheet

4 in 1 Grout Additive



Concentrated grout additive designed to increase the flexibility, strength and water resistance of cement based grouts



WHERE TO USE

Surfaces

Suitable for use when grouting over fibre cement sheet floors and swimming pools.

Areas

Suitable for interior and exterior domestic applications. Ideal for submerged and high foot traffic areas, where a high degree of deformability is required.

PRODUCT INFORMATION

VOC Content

Low VOC - Specification for V2 IEQ-13, V1.1 IEQ-11

FEATURES & BENEFITS

- Increases flexibility, strength and water resistance of cement based grout
- Enhances the colour of grout

PACKAGING

- Available in a 1L or 5L jerry can



MADE IN AUSTRALIA



DIRECTIONS FOR USE

- Test the product in an inconspicuous area first for colour matching

ADDITIVE PREPARATION

- Davco 4 in 1 Grout Additive must be diluted with clean, potable water at a ratio of 1:1 for use as an additive in cement based grouts. Thoroughly mix the required amount of 4 in 1 Grout Additive and water together as per the following:

GROUT	4 IN 1 GROUT ADDITIVE	WATER
Davco Elite ColourGrout - 1kg	125ml	125ml
Davco Superfine White Grout - 1kg	125ml	125ml
Davco Sanitized® Colorgrout - 1kg	125ml	125ml
Davco Slate & Quarry Grout - 1kg	100ml	100ml

GROUT MIX PROCESS

1. Add the required amount of 4 in 1 Grout Additive and water mixture into a clean bucket.
2. Slowly add the powder to the liquid while mixing by hand or with a mixing paddle attached to a drill.
3. Continue to mix for several minutes until a toothpaste-like consistency is achieved, free of lumps of powder.
4. Allow mixture to stand for 5 minutes, remix then use the grout.

APPLICATION

- The grout should be applied as per the instructions for the grout, including joint shaping and clean up
- Once the grout has sufficiently hardened, the tiles should be polished with a dry cloth. Ensure the face of the tiles are cleaned and polished within 4-6 hours
- For difficult to remove areas, it is recommended to use Davco Sanitized® Tile and Grout Cleaner

- For natural stone and course surface applications, it is recommended to reseat the tile surface before grouting

Note: 4 in 1 Grout Additive will increase the tackiness of the grout as well as reduce the pot life, open time, work time and final clean up time

Clean-up & Return to Service

- Clean tools and equipment with water before the grout dries
- Follow the return to service instructions for the grout

PRECAUTIONS

Safety

- SDS is available from www.parexdavco.com.au
- It is recommended that applicators wear PVC or similar gloves and safety goggles while handling this product
- Keep out of reach of children. If eye contact occurs, rinse with cool water
- If ingested get immediate medical assistance

General

- Do not use in temperatures above 35°C or below 5°C
- Do not allow the product to freeze

Specific

- Not suitable for areas where high chemical and stain resistance is required use Davco Grout Cure or Davco Epoxy Grout
- 4 in 1 Grout Additive will make the grout a slightly darker shade than when mixed with clean potable water
- For situations not mentioned in this technical data sheet, contact ParexGroup


TECHNICAL

TECHNICAL DATA	4 in 1 Grout Additive
Appearance	White liquid
Specific gravity of mix	1.0kg/L
Flash point	Non flammable
Shelf life when stored unopened in an elevated, cool, dry location	12 months

All measurements are taken at 22°C and 50% relative humidity. Specifications vary according to site conditions and should be taken as a guide only.



ParexGroup products manufactured in Australia are produced in accordance with quality management systems certified as complying with AS/NZS ISO 9001:2008.



ParexGroup reserves the right to inspect any alleged failure at our cost. No responsibility will be accepted unless a representative of ParexGroup is afforded the opportunity to inspect any alleged failure.

