

# Tile Grip


## Packaging



## Mixing



## Application



## Uses



## Substrates

Glazed floor tiles  
Do not use on  
wall tiles

## Reduces slip on wet tiled floors

### Description

A liquid specifically designed to reduce the danger of slipping on wet tiles. It is recommended for use only on hard, thick floor glazes, i.e. mosaic and ceramic floor tiles.

### Precautions

**A sacrificial or inconspicuous test tile must be used to check suitability. Do not use on wall tiles.**

### Uses

Floor areas subject to slipping when the surface is wet, i.e.:

- Home bathroom and kitchen
- Pool surrounds
- Hospitals
- Any glazed tiled surfaces
- Nursing homes
- Shopping centres
- Restaurants

### Coverage (Approximately)

1 litre covers approximately 10-12m<sup>2</sup>, depending on surface type.

### Surface Preparation

Requires floor to be thoroughly cleaned prior to application. All waxes and contaminants must be removed.

**The surface must be wet before application.**

### Application

Pour into a painters tray and **apply with a sponge or pad applicator (do not use a roller)**. Spread the liquid evenly over the floor ensuring all areas are completely covered. **Allow the Tile Grip to work for only 10 minutes** and then it must be completely removed by thorough washing with plenty of **clean water**. **Never allow Tile Grip to dry on the surface of the tile as it may affect the tile's appearance.** Do not allow contact with metals as discolouration may occur. Do not mix with other cleaning solutions or acids. **Avoid contact with wall tiles. Impervious gloves and goggles must be worn during application.**

**Tile Grip** works by roughening the surface of the glaze. **Tile Grip** can reduce the effectiveness of the glaze and/or discolour the tile if directions are not strictly adhered to.

**A test area must be done to determine the suitability for its intended use.** If this treatment is not satisfactory, replacement of the tiles with a non-slip tile is the only option.

### Performance Data

Many tile surfaces are slippery when wet (i.e., have a very low coefficient of friction). **Tile Grip** can increase the coefficient of friction and reduce slip by as much as 70% on slippery floors.

### Specification

The anti-slip treatment for the ceramic floor tiles shall reduce slip by up to 70% and not alter the surface appearance, such as **Tile Grip** manufactured by **Construction Chemicals**, and shall be applied in accordance with the manufacturer's application instructions.

### Warnings

- Highly corrosive
- Contact with eyes, even for a short period can cause blindness
- Use with adequate ventilation

### Safety Directions

- Avoid contact with eyes - wear goggles
- Avoid contact with skin - wear rubber gloves
- Avoid breathing spray mist or vapour

### First Aid

**Eye** - If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

**Inhalation** - If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator where an inhalation risk exists. Apply artificial respiration if not breathing.

**Skin** - If skin contact occurs, immediately remove contaminated clothing. Flush skin under running water for 15 minutes. Then apply calcium gluconate gel. Contact a Poisons Information Centre on 13 11 26 (Australia Wide).

**Ingestion** - For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.

### Shelf Life

2 years