



UNIVERSAL PRIMER

Product Description:

- RLA Universal primer is a rapid drying solvent free low VOC water based acrylic primer.
- For use over porous and non porous substrates such as existing tiles, old paint (with the exception of oil based paints), vinyl adhesive, vinyl tiles, carpet adhesive residue, metal surfaces, sealed or burnished concrete floors.
- RLA Universal Primer is compatible with cement based ceramic tile adhesives.

Substrates:

- RLA Universal Primer can be applied internally or externally over clean dry surfaces.

Sub Floor Preparation:

- Sub floor must be free of oil, grease, wax, curing compounds, dust, old adhesive and any other contamination, which may inhibit bond.
Note:
- Concrete floors must be dry in accordance with A.S.3958.1-2007.
- Where temperature less than 5°C or greater than 30°C is encountered, contact our technical staff for specific advice.

Application

Porous Substrates:

- Priming of standard concrete surfaces, dilute Universal primer using 4 parts clean water and 1 part Universal primer.
- Apply primers using a roller, brush or broom, ensuring entire area is completely primed.
- Very absorbent concrete may require a second coat of Universal primer diluted 1 part Primer with 4 parts water
- Allow to cure for 30 minutes.

Non - Porous Substrates:

- Apply and even layer of Universal Primer neat (undiluted to non porous substrates)
- Allow primer to dry to a clear film (approximately 2 hours @ 25°C.)
- Once Universal primer is tack free green film, only then can a topping such as tile adhesives or levelling compounds be applied over Universal Primer.

Mixing:

- Thoroughly mix primer before use.

Clean up:

- Clean all equipment with water immediately after use.

Coverage:

- Approximately 5m² to 10m² per Litre.

Packaging:

- Universal Primer – 1lt and 5lt jerry cans.

Rapid Drying Solvent Free

Low VOC

Water Based Acrylic Primer

**Porous and Non Porous
Substrates**

**Internal & External
Applications**

Dries Green



Shelf life:

- 12 months in unopened containers.

Storage:

- Universal primer must be stored in a dry area off the ground, out of direct sun light, protect from frost.

Initial Set Times:

- 1-2 hours @ 25°C.

Safety and Handling:

- Material Safety Data Sheet available upon request.

Restrictions:

- Do not apply Universal primer on substrates subject to rising damp.
- Do not apply Universal primer at thickness greater than 1mm thick
- Do not apply Primer on tiles that have wax or excessively high gloss coating

Note:

- The supplied information is based on our experience and is to be regarded as general instructions.
- We can not guarantee successful results as we do not have any influence on the conditions at the construction site.
- In any case a test area is highly recommended before installation.

Disclaimer: The information supplied is to the best of our knowledge true and accurate. The actual application of the product is beyond the manufacturers control. Any failure or damage caused by the incorrect usage of the product is not the responsibility of the manufacturer. The manufacturer insists that all workmanship must be carried out in accordance with AS 3958.1-2007. It is also the responsibility of the end user to ensure that the literature in their possession is the latest issue.



www.rlapolymers.com.au

TECHNICAL ENQUIRIES TOLL FREE No.1800 752 679

Head Office:

215 Colchester Rd,
Kilsyth, VIC 3137
Ph: (03) 9728 1644
Fax: (03) 9728 6009

NSW:

363 Wentworth Ave,
Pendle Hill, NSW 2145
Ph: (02) 9636 7444
Fax: (02) 9636 7688

Queensland:

25 Computer Rd,
Yatala, QLD 4207
Ph: (07) 3807 4022
Fax: (07) 3807 4755

South Australia:

Blade Runner Distributors
2 Seaforth Ave,
Somerton Park, SA 5044
Ph: (08) 8358 5200
Fax: (08) 8358 5300

Western Australia:

Ph: 1800 242 931

New Zealand:

67 Dalgety Dr,
Manukau City
Auckland, NZ
Ph: 649 267 2772

Issue Date - 24.08.2011